



MOUNTING PLATE NSX/CVS/
VIGI/INS 250 V. FIX.TOGGLE

03050

⚠ Toote tootmise lõpetamisest teatamise kuupäev 14. veebr 2024

⚠ Tootmisest maas

Peamine

Vahemik	Prisma
Tootevalik	Prisma G
Toote Või Komponenti Tüüp	Mounting plate
Lisavarustus / Eraldi Osa Kategooria	Paigaldustarvik
Ühilduvus Tootevalikuga	Prisma Prisma Pack 250 duct Prisma Prisma G duct Prisma Prisma P cubicle
Installation Description	Floor-standing duct 300 mm Wall-mounted duct 300 mm Cubicle 400 mm 400 mm Pack enclosure 300 mm
Installed Device	EasyPact fixed CVS100...160 without toggle - vertikaalne EasyPact fixed CVS250 without toggle - vertikaalne ComPact fixed INS250 direct front rotary handle - vertikaalne ComPact fixed INV100 direct front rotary handle - vertikaalne ComPact fixed INV160 direct front rotary handle - vertikaalne ComPact fixed INV200 direct front rotary handle - vertikaalne ComPact fixed INV250 direct front rotary handle - vertikaalne ComPact fixed NSX100...160 without toggle - vertikaalne ComPact fixed NSX250 without toggle - vertikaalne EasyPact fixed CVS100...160 with toggle - vertikaalne EasyPact fixed CVS250 with toggle - vertikaalne ComPact fixed NSX100...160 with toggle - vertikaalne ComPact fixed NSX250 with toggle - vertikaalne ComPact plug-in NSX100...160 without toggle - vertikaalne ComPact plug-in NSX250 without toggle - vertikaalne ComPact plug-in NSX100...160 with toggle - vertikaalne ComPact plug-in NSX250 with toggle - vertikaalne
Poles Description	1 x 3P fixed INS250 vertikaalne 1 x 4P fixed INS250 vertikaalne 1 x 3P fixed INV250 vertikaalne 1 x 4P fixed INV250 vertikaalne 1 x 3P fixed INV100 vertikaalne 1 x 4P fixed INV100 vertikaalne 1 x 3P fixed INV160 vertikaalne 1 x 4P fixed INV160 vertikaalne 1 x 3P fixed INV200 vertikaalne 1 x 4P fixed INV200 vertikaalne 1 x 3P fixed CVS100...160 vertikaalne 1 x 4P fixed CVS100...160 vertikaalne 1 x 3P fixed CVS250 vertikaalne 1 x 4P fixed CVS250 vertikaalne 1 x 3P fixed NSX100...160 vertikaalne 1 x 4P fixed NSX100...160 vertikaalne 1 x 3P plug-in NSX100...160 vertikaalne 1 x 4P plug-in NSX100...160 vertikaalne 1 x 3P fixed NSX250 vertikaalne 1 x 4P fixed NSX250 vertikaalne 1 x 3P plug-in NSX250 vertikaalne 1 x 4P plug-in NSX250 vertikaalne

Suurim lubatud võrreldavate toodete arv on täis. Avage jaotis Võrrelda tooteid #.LNK# ja kustutage jätkamiseks mõni toode

Condition Of Using Cable Tie	Need additional plate 1 vertikaalne
Number Of Vertical Modules [50 Mm]	9 CVS100...160 without, direct with long terminal shield 300 mm floor-standing duct top or bottom 9 CVS100...160 without, direct with long terminal shield 300 mm wall-mounted duct top or bottom 9 CVS100...160 without, direct with long terminal shield 300 mm Pack enclosure top or bottom 9 CVS250 without, direct with long terminal shield 300 mm floor-standing duct top or bottom 9 CVS250 without, direct with long terminal shield 300 mm wall-mounted duct top or bottom 9 CVS250 without, direct with long terminal shield 300 mm Pack enclosure top or bottom 9 INS250, direct with long terminal shield 300 mm floor-standing duct top or bottom 9 INS250, direct with long terminal shield 300 mm wall-mounted duct top or bottom 9 INV100, direct with long terminal shield 300 mm floor-standing duct top or bottom 9 INV100, direct with long terminal shield 300 mm wall-mounted duct top or bottom 9 INV160, direct with long terminal shield 300 mm floor-standing duct top or bottom 9 INV160, direct with long terminal shield 300 mm wall-mounted duct top or bottom 9 INV200, direct with long terminal shield 300 mm floor-standing duct top or bottom 9 INV200, direct with long terminal shield 300 mm wall-mounted duct top or bottom 9 INV250, direct with long terminal shield 300 mm floor-standing duct top or bottom 9 INV250, direct with long terminal shield 300 mm wall-mounted duct top or bottom 9 NSX100...160 without, direct with long terminal shield 300 mm floor-standing duct top or bottom 9 NSX100...160 without, direct with long terminal shield 300 mm wall-mounted duct top or bottom 9 NSX100...160 without, front connection 400 mm cubicle 9 NSX100...160 without, direct with long terminal shield 300 mm Pack enclosure top or bottom 9 NSX250 without, direct with long terminal shield 300 mm floor-standing duct top or bottom 9 NSX250 without, direct with long terminal shield 300 mm wall-mounted duct top or bottom 9 NSX250 without, front connection 400 mm cubicle 9 NSX250 without, direct with long terminal shield 300 mm Pack enclosure top or bottom 13 CVS100...160 with, direct with long terminal shield 300 mm floor-standing duct top or bottom 13 CVS100...160 with, direct with long terminal shield 300 mm wall-mounted duct top or bottom 13 CVS250 with, direct with long terminal shield 300 mm floor-standing duct top or bottom 13 CVS250 with, direct with long terminal shield 300 mm wall-mounted duct top or bottom 13 NSX100...160 with, direct with long terminal shield 300 mm floor-standing duct top or bottom 13 NSX100...160 with, direct with long terminal shield 300 mm wall-mounted duct top or bottom 11 NSX100...160 with, front connection 400 mm cubicle 13 NSX100...160 with, direct with long terminal shield 300 mm Pack enclosure top or bottom 13 NSX250 with, direct with long terminal shield 300 mm floor-standing duct top or bottom 13 NSX250 with, direct with long terminal shield 300 mm wall-mounted duct top or bottom 11 NSX250 with, front connection 400 mm cubicle 13 NSX250 with, direct with long terminal shield 300 mm Pack enclosure top or bottom
Standardid	IEC 61439-2
Toote Sertifikaadid	ASEFA

Täiendav

Kaitsekäitlus	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Pinna Viimistlus	Matt Smooth
Värv	Valge (RAL 9001)
Laius	300 mm
Kõrgus	250 mm

Netokaal

0,54 kg

Functional Unit

[illegible]

[illegible]

Pakendiüksused

Pakendi Tüüp 1	PCE
Ühikute Arv Pakendis 1	1
Package 1 Height	5,500 cm
Pakendi Laius 1	16,000 cm
Pakendi Pikkus 1	22,000 cm
Pakendi Kaal 1	600,000 g
Pakendi Tüüp 2	S04
Ühikute Arv Pakendis 2	30
Pakendi Kõrgus 2	30,000 cm
Pakendi Laius 2	40,000 cm
Pakendi Pikkus 2	60,000 cm
Pakendi Kaal 2	18,703 kg
Pakendi Tüüp 3	P12
Ühikute Arv Pakendis 3	240
Pakendi Kõrgus 3	105,000 cm
Pakendi Laius 3	80,000 cm
Pakendi Pikkus 3	120,000 cm
Pakendi Kaal 3	161,624 kg

Jätkusuutlikus

Green Premium™ ökomärgistus on Schneider Electricu kohustus pakkuda tooteid oma klassi parima keskkonnatoimega. Green Premium lubab järgida uusimaid määrusi, keskkonnamõjude läbipaistvust ning ringid- ja madala CO₂-heitega tooteid.

Toote jätkusuutlikkuse hindamise juhend on valge raamat, mis selgitab globaalseid ökomärgise standardeid ja seda, kuidas keskkonnadeklaratsioone tõlgendada.

[Juhis kaubandusliku toote jätkusuutlikkuse hindamiseks >](#)



Läbipaistvus RoHS/REACH

Heaolu tulemuslikkus

✓	Ilma Svhc Reach-Ta	
✓	Mürgiste Raskemetallideta	
✓	Elavhõbedavaba	
✓	Rohs Eranditeave	Jah
✓	Halogeenivabade Plastosadega Toode	

Sertifikaadid ja standardid

Eli Rohs Direktiiv	Ennetav vastavus (toode ei jää EL-i RoHS seadustega määratud piiridesse) ELi RoHS deklaratsioon
Hiina Eohs Regulatsioon	Hiina RoHS deklaratsioon Ennetav Hiina RoHS deklaratsioon (ei kuulu Hiina RoHS-i õigussfääri)
Keskkonnaalane Avaldus	Toote keskkonnaprofiil